



Video Surveillance / IP Video Recorders (NVR)

DAHUA DHI-NVR4208-8P-4KS3

Brand Dahua
Model NVR4208-8P-4KS3
Warranty 12 months

Price as of 22.10.2026

712.00 ₾

VAT included


Current price and stock: online
<https://alldigital.ge/en/dahua-dhi-nvr4208-8p-4ks3>

Key specs

Megapixels

12 MP

Recording Resolution

12MP, 4K (8MP), 6MP, 5MP, 4MP, 3MP, 1080P (2MP), 720P

Recorder Type

NVR

HDD Bays

2

Channels

8

Camera

Megapixels	12 MP
------------	-------

Image & Video

Frame Rate	30 fps
------------	--------

Compression	H.265/H.264/MJPEG
-------------	-------------------

Network

Network Interface	1 × RJ-45, 10/100/1000 Mbps
-------------------	-----------------------------

Incoming Bandwidth	160 Mbps
--------------------	----------

Outgoing Bandwidth	160 Mbps
--------------------	----------

ONVIF	Yes
-------	-----

Power & Protection

Power Supply	100–240 VAC, 50/60 Hz
--------------	-----------------------

Power Input	100–240 VAC, 50/60 Hz
-------------	-----------------------

Recording

Decoding capability	AI off: 1 × 12 MP@30 fps; 2 × 8 MP@30 fps; 2 × 6 MP@30 fps; 3 × 5 MP@30 fps; 4 × 4 MP@30 fps; 8 × 1080p@30 fps; AI on: 1 × 12 MP@30 fps; 1 × 8 MP@30 fps; 2 × 6 MP@30 fps; 2 × 5 MP@30 fps; 3 × 4 MP@30 fps; 7 × 1080p@30 fps
---------------------	---

Recorder Type	NVR
---------------	-----

Recording	
Channels	8
IP Channels	8
Recording Resolution	12MP, 4K (8MP), 6MP, 5MP, 4MP, 3MP, 1080P (2MP), 720P
Signal Support	IP
Recorder Compression	Smart H.265+; H.265; Smart H.264+
Playback	Up to 8 channels
Storage	
HDD Bays	2
Max HDD	20 TB per bay · 40 TB total
Outputs & Audio	
Video Output	1× HDMI, 1× VGA
Audio Input	1 × RCA
Audio Output	1 channel RCA
Smart & Features	
AI Features	SMD, Face Detection, Face Recognition, Perimeter Protection, People Counting, Heat Map
Alarm Input	4 channels
Alarm Output	2 channels (1-channel 12 V 1 A output)
Ports & PoE	
PoE Ports	8
Connectivity	
Compatible software	DMSS, SmartPSS Lite
USB Port	Front: 1 × USB 2.0; rear: 1 × USB 2.0
Compliance	
Certifications	CE
Physical	
Operating humidity	10 ... 93 %
Form Factor / Chassis	1U
Operating Temperature	-10 ... +55 °C (14 ... 131 °F)
Dimensions	375 × 53 × 327.9 mm (14.76 × 2.09 × 12.91 in)
Weight	2.47 kg (5.45 lb)