



Video Surveillance / IP Cameras

HiLook IPC-B640HA-LZU 2.8-12mm 4MP გარე Bullet, Motorized Zoom, Mic, SD, IR 50მ

Brand HiLook
 Model IPC-B640HA-LZU
 Warranty 12 months

Price on request



Current price and stock: online

<https://alldigital.ge/en/hilook-ipc-b640ha-lzu-2-8-12mm-4mp-gare-bullet-motorized-zoom-mic-sd-i>

Key specs

Megapixels

4 MP

IR Range

50 m (164 ft)

Form Factor

Bullet

WDR

120dB True WDR

Focal Length

2.8-12 mm

IP / IK Rating

IP67

Camera

Image Sensor	1/3" CMOS
Max Resolution	2560 × 1440
Megapixels	4 MP
Form Factor	Bullet
Housing Material	Metal
Usage	Outdoor, Indoor
Characteristics	Two-way Audio, Microphone, microSD

Lens

Lens Type	Motorized
Focal Length	2.8-12 mm
Aperture	F1.6
Field of View	Horizontal: 104.3° ~ 27.9°
Lens Mount	M14

Image & Video

Supplement light	Infrared (IR), White light
Min. Illumination	0.005 lux
IR Range	50 m (164 ft)
Day / Night	Day/Night (auto IR-cut)

Image & Video

WDR	120dB True WDR
Frame Rate	20 fps
Compression	Ultra 265 / H.265 / H.264

Audio

Audio	Two-way audio (Built-in mic & speaker)
-------	--

Network

Network Interface	RJ45 10M/100M Base-TX Ethernet
Storage	MicroSD (up to 512GB)

Power & Protection

Power Supply	12V DC / PoE
IP / IK Rating	IP67
Power Consumption	12.9 W

Smart & Features

Features	Smart Hybrid Light, Human Detection, ONVIF
Active Deterrence	Voice Warning

Connectivity

Compatible software	Hik-Connect, iVMS-4200
---------------------	------------------------

Compliance

Certifications	CE
----------------	----

Physical

Operating humidity	≤ 95 %
Operating Temperature	-30 ... +60 °C (-22 ... 140 °F)
Dimensions	Ø105 × 252 mm (Ø4.13 × 9.92 in)
Weight	570 g (20.11 oz)