



Video Surveillance / IP Cameras

## IP კამერა - 5მპ, 1.4მმ, Fisheye, IK10, 360°, Mic, SD, ANR, Uniview

Brand Uniview  
Model IPC815SB-ADF14K-I0  
Warranty 12 months

Price as of 22.10.2026

**874.80** ₾

VAT included


**Current price and stock: online**
<https://alldigital.ge/en/ip-kamera-5mp-1-4mm-fisheye-ik10-360-mic-sd-anr-uniview>

### Key specs

Megapixels

**5 MP**

IR Range

**10 m (32.8 ft)**

Form Factor

**Fisheye**

WDR

**120 dB**

Focal Length

**1.4 mm**

IP / IK Rating

**IP66, IK10**

### Camera

|                  |             |
|------------------|-------------|
| Image Sensor     | 1/2.8"      |
| Max Resolution   | 2592 × 1944 |
| Megapixels       | 5 MP        |
| Form Factor      | Fisheye     |
| Housing Material | Metal       |
| Usage            | Indoor      |
| Characteristics  | Microphone  |

### Lens

|               |        |
|---------------|--------|
| Lens Type     | Fixed  |
| Focal Length  | 1.4 mm |
| Aperture      | F2.0   |
| Field of View | 360°   |

### Image & Video

|                   |                         |
|-------------------|-------------------------|
| Supplement light  | Infrared (IR)           |
| Min. Illumination | 0.01 Lux                |
| IR Range          | 10 m (32.8 ft)          |
| Day / Night       | Day/Night (auto IR-cut) |
| WDR               | 120 dB                  |

|                               |                                      |
|-------------------------------|--------------------------------------|
| <b>Image &amp; Video</b>      |                                      |
| Frame Rate                    | 30 fps                               |
| Compression                   | Ultra 265, H.265, H.264, MJPEG       |
| <b>Audio</b>                  |                                      |
| Audio                         | Built-in mic                         |
| <b>Network</b>                |                                      |
| Network Interface             | 1 × RJ45 10 M/100 M Base-TX Ethernet |
| Storage                       | MicroSD up to 512 GB                 |
| <b>Power &amp; Protection</b> |                                      |
| Power Supply                  | DC 12 V±25%, PoE (IEEE 802.3af)      |
| IP / IK Rating                | IP66, IK10                           |
| Power Consumption             | 8.5 W                                |
| Surge Protection              | 4 kV                                 |
| <b>Outputs &amp; Audio</b>    |                                      |
| Audio Input                   | 1                                    |
| Audio Output                  | 1                                    |
| <b>Smart &amp; Features</b>   |                                      |
| Features                      | ONVIF                                |
| Alarm Input                   | 1                                    |
| Alarm Output                  | 1                                    |
| <b>Connectivity</b>           |                                      |
| Compatible software           | Uniview EZView / EZStation           |
| <b>Compliance</b>             |                                      |
| Certifications                | CE, FCC, UL                          |
| <b>Physical</b>               |                                      |
| Operating humidity            | ≤ 95 %                               |
| Operating Temperature         | -30 ... +60 °C (-22 ... 140 °F)      |
| Dimensions                    | Ø125 × 43.7 mm (Ø4.92 × 1.72 in)     |
| Weight                        | 360 g (12.7 oz)                      |