



Video Surveillance / IP Cameras

IPC-HDBW2449F-AS-E2-IL 2.8mm 2 მოდულიანი 4მპ ქსელ. კამ IK10, IP67, Mic/Aud-in, IR/Warm light

Brand Dahua
Model IPC-HDBW2449F-AS-E2-IL-2.8
Warranty 12 months

Price as of 23.10.2026

468.76 ₾

VAT included


Current price and stock: online

<https://alldigital.ge/en/ipc-hdbw2449f-as-e2-il-2-8mm-2-moduliani-4mp-kse1-kam-ik10-ip67-mic-au>

Key specs

Megapixels

4 MP

IR Range

30 m (98.4 ft)

Form Factor

Dome

WDR

120dB

Focal Length

2.8 mm

IP / IK Rating

IP67; IK10

Camera

Image Sensor	Channel 1: 1/2.7" CMOS; Channel 2: 1/2.7" CMOS
Max Resolution	Channel 1: 2688 (H) × 1520 (V); Channel 2: 2688 (H) × 1520 (V)
Megapixels	4 MP
Form Factor	Dome
Housing Material	Metal
Characteristics	Microphone, microSD

Lens

Lens Type	Fixed
Focal Length	2.8 mm
Aperture	2.8mm: F1.6 3.6mm: F1.6
Field of View	2.8 mm: H 101.5° / V 54.7° / D 120.8°; 3.6 mm: H 82.7° / V 45.3° / D 96.6°
Lens Mount	Channel 1: M12; Channel 2: M12

Image & Video

Supplement light	Infrared (IR), Warm light
Min. Illumination	0.006 lux@F1.6 (Color); 0.0006 lux@F1.6 (B/W); 0 lux (Illuminator on)
IR Range	30 m (98.4 ft)
Day / Night	Day/Night (auto IR-cut)

Image & Video	
WDR	120dB
Frame Rate	20 fps
Compression	H.265; H.264; H.264H
Audio	
Audio	PCM; G.711a; G.711Mu; G.726; G.723
Network	
Network Interface	RJ-45 (10/100/1000 Base-T)
Storage	FTP; SFTP; Micro SD card (support max. 256 GB); NAS
Power & Protection	
Power Supply	12 VDC/PoE+ (802.3at)
IP / IK Rating	IP67; IK10
Power Consumption	15.8 W
Outputs & Audio	
Audio Input	1 channel (RCA port)
Audio Output	1 channel (RCA port)
Smart & Features	
Features	Smart Hybrid Light
Alarm Input	1-channel input: wet contact, 5 mA 3–5 VDC
Alarm Output	1 output; wet contact, 300 mA 12 VDC
Connectivity	
Compatible software	DMSS, SmartPSS Lite
Compliance	
Certifications	CE
Physical	
Operating humidity	≤ 95 %
Operating Temperature	-40 ... +60 °C (-40 ... 140 °F)
Dimensions	84 × 69.4 × 164 mm (3.31 × 2.73 × 6.46 in)
Weight	630 g (22.22 oz)