



Video Surveillance / IP Cameras

IPC-HDBW2541R-ZAS 2.7-13.5mm 5მპ Dome ქსელური კამერა IP67/IK10, Mic, Aud-in, IR 40მ-მდე

Brand Dahua
Model IPC-HDBW2541R-ZAS-2.713.5
Warranty 12 months

Price as of 22.10.2026

593.76 ₾

VAT included


Current price and stock: online

<https://alldigital.ge/en/ipc-hdbw2541r-zas-2-7-13-5mm-5mp-dome-kseluri-kamera-ip67-ik10-mic-aud>

Key specs

Megapixels

5 MP

IR Range

40 m (131.2 ft)

Form Factor

Dome

WDR

120 dB

Focal Length

2.7–13.5 mm

IP / IK Rating

IP67; IK10

Camera

Image Sensor	1/2.7" CMOS
Max Resolution	2960 (H) × 1668 (V)
Megapixels	5 MP
Form Factor	Dome
Housing Material	Metal
Characteristics	Microphone, microSD

Lens

Lens Type	Motorized
Focal Length	2.7–13.5 mm
Aperture	F1.5
Field of View	H: 113°–31°; V: 58°–18°; D: 138°–36°
Lens Mount	φ14

Image & Video

Supplement light	Infrared (IR)
Min. Illumination	0.007 lux@F1.5 (Color); 0.0007 lux@F1.5 (B/W); 0 lux (Illuminator on)
IR Range	40 m (131.2 ft)
Day / Night	Day/Night (auto IR-cut)

Image & Video	
WDR	120 dB
Frame Rate	20 fps
Compression	H.265; H.264; H.264H
Audio	
Audio	G.711a; G.711Mu; PCM; G.726
Network	
Network Interface	RJ-45 (10/100 Base-T)
Storage	FTP; SFTP; Micro SD card (support max. 256 GB); NAS
Power & Protection	
Power Supply	12 VDC/PoE (802.3af)
IP / IK Rating	IP67; IK10
Power Consumption	7.4 W
Outputs & Audio	
Audio Input	1 channel (RCA port)
Audio Output	1 channel (RCA port)
Smart & Features	
Features	Line Crossing, Intrusion Detection
Alarm Input	1-channel input: 5mA 3V–5V DC
Alarm Output	1-channel output: 300mA 12V DC
Connectivity	
Compatible software	DMSS, SmartPSS Lite
Compliance	
Certifications	CE, FCC, UL
Physical	
Operating humidity	≤ 95 %
Operating Temperature	-30 ... +60 °C (-22 ... 140 °F)
Dimensions	Ø122 × 93.4 mm (Ø4.8 × 3.68 in)
Weight	510 g (17.99 oz)