Kutaisi, 1–3 Aghmashenebeli Ave. | Mon–Sat · 10:00–19:00 +995 431 24 60 07 | +995 555 61 55 61 info@alldigital.ge | alldigital.ge
WhatsApp / Viber: +995 555 61 55 61

Video Surveillance / IP Cameras

IPC-HDBW2841R-ZAS 2.7-13.5mm 8მპ Dome ქსელური კამერა IP67/IK10, Mic, Aud-in, IR 40მ-მდე

Brand	Dahua
Model	IPC-HDBW2841R-ZAS-2.713.5
Warranty	12 months

Price as of 22.10.2026

664.07 ₾

VAT included

Current price and stock: online

https://alldigital.ge/en/ipc-hdbw2841r-zas-2-7-13-5mm-8mp-dome-kseluri-kamera-ip67-ik10-mic-aud

Key specs

Megapixels **8 MP**	Form Factor **Dome**	Focal Length **2.7–13.5 mm**
IR Range **40 m** (131.2 ft)	WDR **120 dB**	IP / IK Rating **IP67; IK10**

Camera

Image Sensor	1/2.7" CMOS
Max Resolution	3840 (H) × 2160 (V)
Megapixels	8 MP
Form Factor	Dome
Housing Material	Metal
Characteristics	Microphone, microSD

Lens

Lens Type	Motorized
Focal Length	2.7–13.5 mm
Aperture	F1.5
Field of View	H: 113°–31°; V: 58°–18°; D: 138°–36°
Lens Mount	φ14

Image & Video

Supplement light	Infrared (IR)
Min. Illumination	0.008 lux@F1.5 (Color); 0.0008 lux@F1.5 (B/W); 0 lux (Illuminator on)
IR Range	40 m (131.2 ft)
Day / Night	Day/Night (auto IR-cut)

Image & Video

WDR	120 dB
Frame Rate	20 fps
Compression	H.265; H.264; H.264H

Audio

Audio	G.711a; G.711Mu; PCM; G.726

Network

Network Interface	RJ-45 (10/100 Base-T)
Storage	FTP; SFTP; Micro SD card (support max. 256 GB); NAS

Power & Protection

Power Supply	12 VDC/PoE (802.3af)
IP / IK Rating	IP67; IK10
Power Consumption	7.3 W

Outputs & Audio

Audio Input	1 channel (RCA port)
Audio Output	1 channel (RCA port)

Smart & Features

Features	Line Crossing, Intrusion Detection
Alarm Input	1-channel input: 5mA 3V–5 VDC
Alarm Output	1-channel output: 300mA 12 VDC

Connectivity

Compatible software	DMSS, SmartPSS Lite

Compliance

Certifications	CE, FCC, UL

Physical

Operating humidity	≤ 95 %
Operating Temperature	-30 ... +60 °C (-22 ... 140 °F)
Dimensions	Ø122 × 93.4 mm (Ø4.8 × 3.68 in)
Weight	510 g (17.99 oz)