Kutaisi, 1–3 Aghmashenebeli Ave. | Mon–Sat · 10:00–19:00 +995 431 24 60 07 | +995 555 61 55 61 info@alldigital.ge | alldigital.ge
WhatsApp / Viber: +995 555 61 55 61

Video Surveillance / IP Cameras

# IPC-HDW2441T-ZS 2.7-13.5mm 4მპ Eyeball ქსელური კამერა მეტ. კორპუსი IP67, Mic, IR 40მ-მდე

| | |
|---|---|
| Brand | Dahua |
| Model | IPC-HDW2441T-ZS-2.713.5 |
| Warranty | 12 months |

Price as of 22.10.2026
**486.99 ₾**
VAT included

**Current price and stock: online**
https://alldigital.ge/en/ipc-hdw2441t-zs-2-7-13-5mm-4mp-eyeball-kseluri-kamera-met-korpusi-ip67

## Key specs

| | | |
|---|---|---|
| Megapixels<br>**4 MP** | Form Factor<br>**Turret** | Focal Length<br>**2.7–13.5 mm** |
| IR Range<br>**40 m** (131.2 ft) | WDR<br>**120 dB** | IP / IK Rating<br>**IP67** |

## Camera

| | |
|---|---|
| Image Sensor | 1/2.9" CMOS |
| Max Resolution | 2688 (H) × 1520 (V) |
| Megapixels | 4 MP |
| Form Factor | Turret |
| Housing Material | Metal |
| Characteristics | Microphone, microSD |

## Lens

| | |
|---|---|
| Lens Type | Motorized |
| Focal Length | 2.7–13.5 mm |
| Aperture | F1.5 |
| Field of View | H: 104°–29°; V: 54°–16°; D: 125°–34° |
| Lens Mount | φ14 |

## Image & Video

| | |
|---|---|
| Supplement light | Infrared (IR) |
| Min. Illumination | 0.006 lux@F1.5 (Color); 0.0006 lux@F1.5 (B/W); 0 lux (Illuminator on) |
| IR Range | 40 m (131.2 ft) |
| Day / Night | Day/Night (auto IR-cut) |

### Image & Video

| | |
|---|---|
| WDR | 120 dB |
| Frame Rate | 20 fps |
| Compression | H.265; H.264; H.264H |

### Audio

| | |
|---|---|
| Audio | G.711a; G.711Mu; G.726; PCM |

### Network

| | |
|---|---|
| Network Interface | RJ-45 (10/100 Base-T) |
| Storage | FTP; SFTP; Micro SD card (support max. 256 GB) |

### Power & Protection

| | |
|---|---|
| Power Supply | 12 VDC/PoE (802.3af) |
| IP / IK Rating | IP67 |
| Power Consumption | 7.3 W |

### Smart & Features

| | |
|---|---|
| Features | Line Crossing, Intrusion Detection |

### Connectivity

| | |
|---|---|
| Compatible software | DMSS, SmartPSS Lite |

### Compliance

| | |
|---|---|
| Certifications | CE, FCC, UL |

### Physical

| | |
|---|---|
| Operating humidity | ≤ 95 % |
| Operating Temperature | -30 ... +60 °C (-22 ... 140 °F) |
| Dimensions | Ø122 × 108.3 mm (Ø4.8 × 4.26 in) |
| Weight | 690 g (24.34 oz) |