



Video Surveillance / IP Cameras

IPC-HDW8441X-3D 2.8mm ქსელური მთვლედი People counting კამერა WizMind Dual-Lens

Brand Dahua
Model IPC-HDW8441X-3D-2.8
Warranty 12 months

Price as of 23.10.2026

1 463.56 ₾

VAT included


Current price and stock: online

<https://alldigital.ge/en/ipc-hdw8441x-3d-2-8mm-kseluri-mtvleli-people-counting-kamera-wizmind-d>

Key specs

Megapixels

4 MP

IR Range

20 m (65.6 ft)

Form Factor

Turret

WDR

120 dB

Focal Length

2.8 mm

IP / IK Rating

IP67; IK10

Camera

Image Sensor	1/2.8" CMOS
Max Resolution	2560 (H) × 1440 (V)
Megapixels	4 MP
Form Factor	Turret
Housing Material	Metal
Characteristics	Microphone, microSD

Lens

Lens Type	Fixed
Focal Length	2.8 mm
Aperture	2.0 mm: F2.0 2.8 mm: F1.6
Field of View	2.0 mm: H 122° / V 72° / D 141°; 2.8 mm: H 95° / V 52° / D 114°
Lens Mount	M12

Image & Video

Supplement light	Infrared (IR)
Min. Illumination	2.0 mm: 0.007 lux@F2.0 (Color); 2.0 mm: 0.0007 lux@F2.0 (B/W); 2.0 mm: 0 lux (Illuminator on); 2.8 mm: 0.005 lux@F1.6 (Color); 2.8 mm: 0.0005 lux@F1.6 (B/W); 2.8 mm: 0 lux (Illuminator on)
IR Range	20 m (65.6 ft)

Image & Video	
Day / Night	Day/Night (auto IR-cut)
WDR	120 dB
Frame Rate	25/30 fps
Compression	H.265; H.264; H.264H
Audio	
Audio	PCM; G.711a; G.711Mu; G.726; G.723
Network	
Network Interface	RJ-45 (10/100/1000 Base-T)
Storage	FTP; SFTP; Micro SD card (max. 512 GB); NAS
Power & Protection	
Power Supply	12 VDC/PoE (802.3af)
IP / IK Rating	IP67; IK10
Power Consumption	12.9 W
Outputs & Audio	
Audio Input	2 channels (RCA port)
Audio Output	1 channel (RCA port)
Smart & Features	
Features	Line Crossing, Intrusion Detection
Alarm Input	2-channel input: 5 mA 3 V–5 VDC
Alarm Output	2-channel output: 300 mA 12 VDC
Connectivity	
Compatible software	DMSS, SmartPSS Lite
Compliance	
Certifications	CE, FCC, UL
Physical	
Operating humidity	≤ 95 %
Operating Temperature	-40 ... +60 °C (-40 ... 140 °F)
Dimensions	78 × 61.6 × 204 mm (3.07 × 2.43 × 8.03 in)
Weight	820 g (28.92 oz)