



Video Surveillance / IP Cameras

IPC-HFW5442T-ASE 2.8mm 4MP Bullet ქსელური კამერა მეტ. კორპ. IP67/IK10, Mic, Aud-in, IR 50მ-მდე

Brand Dahua
Model IPC-HFW5442T-ASE-2.8
Warranty 12 months

Price as of 23.10.2026

859.39 ₾

VAT included


Current price and stock: online

<https://alldigital.ge/en/ipc-hfw5442t-ase-2-8mm-4mp-bullet-kxeluri-kamera-met-korp-ip67-ik10-mi>

Key specs

Megapixels

4 MP

IR Range

80 m (262.5 ft)

Form Factor

Bullet

WDR

140 dB

Focal Length

2.8 mm

IP / IK Rating

IP67; IK10

Camera

Image Sensor	1/1.8" CMOS
Max Resolution	2688 (H) × 1520 (V)
Megapixels	4 MP
Form Factor	Bullet
Housing Material	Metal
Characteristics	Microphone, microSD

Lens

Lens Type	Fixed
Focal Length	2.8 mm
Aperture	F1.6
Field of View	2.8 mm: H 112° / V 58° / D 139°; 3.6 mm: H 88° / V 50° / D 102°; 6 mm: H 61° / V 35° / D 69°
Lens Mount	M12

Image & Video

Supplement light	Infrared (IR)
Min. Illumination	0.0007 lux@F1.6 (Color); 0.0004 lux@F1.6 (B/W); 0 lux (Illuminator on)
IR Range	80 m (262.5 ft)

Image & Video	
Day / Night	Day/Night (auto IR-cut)
WDR	140 dB
Frame Rate	1 fps
Compression	H.265; H.264; H.264H
Audio	
Audio	G.711a; G.711Mu; PCM; G.726; G.723
Network	
Network Interface	RJ-45 (10/100 Enhancement Base-T)
Storage	FTP; SFTP; Micro SD card (max. 1 TB); NAS
Power & Protection	
Power Supply	12 VDC/PoE (802.3af)/ePoE
IP / IK Rating	IP67; IK10
Power Consumption	9.8 W
Outputs & Audio	
Audio Input	1 channel (RCA port)
Audio Output	1 channel (RCA port)
Smart & Features	
Features	Line Crossing, Intrusion Detection
Alarm Input	1-channel input: wet contact, 5mA 3V–5V DC
Alarm Output	1-channel output: wet contact, 300mA 12V DC
Connectivity	
Compatible software	DMSS, SmartPSS Lite
Compliance	
Certifications	CE, FCC, UL
Physical	
Operating humidity	≤ 95 %
Operating Temperature	-40 ... +60 °C (-40 ... 140 °F)
Dimensions	79 × 75.9 × 244.1 mm (3.11 × 2.99 × 9.61 in)
Weight	820 g (28.92 oz)