



Video Surveillance / IP Cameras

## კამერა DS-2CD1143G2-LIU(4mm), 4MP, Dome, Smart Hybrid Light

Brand Hikvision  
Model DS-2CD1143G2-LIU  
Warranty 12 months

Price as of 22.10.2026

**278.00** ₾

VAT included


**Current price and stock: online**
<https://alldigital.ge/en/kamera-ds-2cd1143g2-liu-4mm-4mp-dome-smart-hybrid-light>

### Key specs

Megapixels

**4 MP**

IR Range

**30 m (98.4 ft)**

Form Factor

**Dome**

WDR

**Yes**

Focal Length

**4 mm**

IP / IK Rating

**IP67, IK08**

### Camera

|                  |                     |
|------------------|---------------------|
| Image Sensor     | 1/3" CMOS           |
| Max Resolution   | 2560 × 1440         |
| Megapixels       | 4 MP                |
| Form Factor      | Dome                |
| Housing Material | Metal               |
| Characteristics  | Microphone, microSD |

### Lens

|               |       |
|---------------|-------|
| Lens Type     | Fixed |
| Focal Length  | 4 mm  |
| Aperture      | F1.6  |
| Field of View | 98°   |
| Lens Mount    | M12   |

### Image & Video

|                   |                            |
|-------------------|----------------------------|
| Supplement light  | Infrared (IR), White light |
| Min. Illumination | 0.005 lux                  |
| IR Range          | 30 m (98.4 ft)             |
| Day / Night       | Day/Night (auto IR-cut)    |
| WDR               | Yes                        |

## Image & Video

|             |                   |
|-------------|-------------------|
| Frame Rate  | 25 fps            |
| Compression | H.265/H.264/MJPEG |

## Audio

|       |              |
|-------|--------------|
| Audio | Built-in mic |
|-------|--------------|

## Network

|                   |         |
|-------------------|---------|
| Network Interface | RJ45    |
| Storage           | microSD |

## Power & Protection

|                   |             |
|-------------------|-------------|
| Power Supply      | PoE, 12V DC |
| IP / IK Rating    | IP67, IK08  |
| Power Consumption | 7.5 W       |

## Smart & Features

|          |                    |
|----------|--------------------|
| Features | Smart Hybrid Light |
|----------|--------------------|

## Connectivity

|                     |                        |
|---------------------|------------------------|
| Compatible software | Hik-Connect, iVMS-4200 |
|---------------------|------------------------|

## Compliance

|                |             |
|----------------|-------------|
| Certifications | CE, FCC, UL |
|----------------|-------------|

## Physical

|                       |                                    |
|-----------------------|------------------------------------|
| Operating humidity    | ≤ 95 %                             |
| Operating Temperature | -30 ... +60 °C (-22 ... 140 °F)    |
| Dimensions            | Ø121.4 × 97.7 mm (Ø4.78 × 3.85 in) |
| Weight                | 550 g (19.4 oz)                    |