



Video Surveillance / IP Cameras / PTZ Cameras

SD1A204DB-GNY 2მპ PTZ ქსელური მართვადი კამერა, 4x ოპტ. გადიდება, IP66, IK08, Mic, IR 20მ-მდე

Brand Dahua
Model SD1A204DB-GNY
Warranty 12 months

Price as of 22.10.2026

653.65 ₾

VAT included


Current price and stock: online

<https://alldigital.ge/en/sd1a204db-gny-2mp-ptz-kseluri-martvadi-kamera-4x-opt-gadideba-ip66-ik08>

Key specs

Megapixels

2 MP

Optical Zoom

4 ×

IP / IK Rating

IP66, IK08

Form Factor

PTZ

IR Range

20 m (65.6 ft)

Focal Length

2.8–12 mm

WDR

120 dB

Camera

Image Sensor	1/2.8" CMOS
Max Resolution	1920 (H) × 1080 (V)
Megapixels	2 MP
Form Factor	PTZ
Characteristics	Microphone, microSD

Lens

Focal Length	2.8–12 mm
Optical Zoom	4 ×
PTZ Presets	300
Pan / Tilt Range	Pan: 0° to 355°; tilt: 5° to 90°
Aperture	F1.8–F2.7
Field of View	H: 101.6°–51.9°; V: 53.1°–29.1°; D: 121.8°–59.7°

Image & Video

Supplement light	Infrared (IR)
Min. Illumination	0.005 lux@F1.8 (Color); 0.0005 lux@F1.8 (B/W); 0 lux (illuminator on)

Image & Video	
IR Range	20 m (65.6 ft)
Day / Night	Day/Night (auto IR-cut)
WDR	120 dB
Frame Rate	25/30 fps
Compression	H.264H; H.264B; Smart H.265+
Audio	
Audio	PCM; G.711A; G.711MU; G.726; MPEG2-Layer2; G.722.1
Network	
Network Interface	RJ-45 (10/100 Base-T)
Storage	Micro SD card (512 GB); FTP/SFTP; NAS
Power & Protection	
Power Supply	12 VDC, 2 A ± 10%; PoE (802.3af)
IP / IK Rating	IP66, IK08
Power Consumption	13 W
Surge Protection	6 kV
Outputs & Audio	
Audio Input	1 channel; LINE IN (bare wire); or built-in microphone
Audio Output	1 channel (LINE OUT, bare wire)
Smart & Features	
Features	Line Crossing, Intrusion Detection
Connectivity	
Compatible software	DMSS, SmartPSS Lite
Compliance	
Certifications	CE, FCC
Physical	
Operating humidity	≤ 95 %
Operating Temperature	-30 ... +60 °C (-22 ... 140 °F)
Dimensions	Ø128 × 65.7 mm (Ø5.04 × 2.59 in)
Weight	500 g (17.64 oz)