



Video Surveillance / IP Cameras / PTZ Cameras

## SD2C405NB-GNY-A-PV-S2 4მპ WizSense PTZ ქსელ. მართ. კამ. 5x ოპტ. გად. IP66, IR/Warm light 30მ

Brand Dahua  
Model SD2C405NB-GNY-A-PV-S2  
Warranty 12 months

Price as of 23.10.2026

**492.19 ₾**

VAT included


**Current price and stock: online**

<https://alldigital.ge/en/sd2c405nb-gny-a-pv-s2-4mp-wizsense-ptz-kse1-mart-kam-5x-opt-gad-ip66-i>

### Key specs

Megapixels

**4 MP**

Optical Zoom

**5 ×**

IP / IK Rating

**IP66**

Form Factor

**PTZ**

IR Range

**30 m (98.4 ft)**

Focal Length

**2.7-13.5 mm**

WDR

**120 dB**

### Camera

|                 |                     |
|-----------------|---------------------|
| Image Sensor    | 1/2.8" CMOS         |
| Max Resolution  | 2560 (H) × 1440 (V) |
| Megapixels      | 4 MP                |
| Form Factor     | PTZ                 |
| Characteristics | Microphone, microSD |

### Lens

|                  |                                                       |
|------------------|-------------------------------------------------------|
| Focal Length     | 2.7-13.5 mm                                           |
| Optical Zoom     | 5 ×                                                   |
| PTZ Presets      | 300                                                   |
| Pan / Tilt Range | Pan: 0° to 345°; tilt: 0° to +90°                     |
| Aperture         | F1.6-F3.0                                             |
| Field of View    | H: 96.73°-24.76°; V: 51.98°-13.91°; D: 110.58°-29.74° |

### Image & Video

|                   |                                                                     |
|-------------------|---------------------------------------------------------------------|
| Supplement light  | Infrared (IR), Warm light                                           |
| Min. Illumination | 0.05 lux@F1.6 (Color); 0.005 lux@F1.6 (B/W); 0 lux (Illuminator on) |

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>Image &amp; Video</b>      |                                    |
| IR Range                      | 30 m (98.4 ft)                     |
| Day / Night                   | Day/Night (auto IR-cut)            |
| WDR                           | 120 dB                             |
| Frame Rate                    | 25/30 fps                          |
| Compression                   | Smart H.265+; H.265; Smart H.264+  |
| <b>Audio</b>                  |                                    |
| Audio                         | PCM; G.711a; G.711Mu; G.726        |
| <b>Network</b>                |                                    |
| Network Interface             | RJ-45 (10/100 Base-T)              |
| Storage                       | Micro SD card (Up to 256 GB); FTP  |
| <b>Power &amp; Protection</b> |                                    |
| Power Supply                  | 12 VDC, 1.5 A ± 10% PoE (802.3af)  |
| IP / IK Rating                | IP66                               |
| Power Consumption             | 12.95 W                            |
| Surge Protection              | 2 kV                               |
| <b>Outputs &amp; Audio</b>    |                                    |
| Audio Input                   | 1 channel (built-in microphone)    |
| Audio Output                  | 1 channel (built-in speaker)       |
| <b>Smart &amp; Features</b>   |                                    |
| Features                      | Smart Hybrid Light                 |
| Active Deterrence             | Warning Light, Voice Warning       |
| <b>Connectivity</b>           |                                    |
| Compatible software           | DMSS, SmartPSS Lite                |
| <b>Compliance</b>             |                                    |
| Certifications                | CE                                 |
| <b>Physical</b>               |                                    |
| Operating humidity            | ≤ 95 %                             |
| Operating Temperature         | -30 ... +55 °C (-22 ... 131 °F)    |
| Dimensions                    | Ø129.6 × 155.5 mm (Ø5.1 × 6.12 in) |
| Weight                        | 650 g (22.93 oz)                   |