



Video Surveillance / IP Cameras / PTZ Cameras

SD49225DB-HNY 2მპ WizSense PTZ ქსელური მართვადი კამერა, 25x ოპტ. გადიდება, IP66, IR 100მ-მდე

Brand Dahua
 Model SD49225DB-HNY
 Warranty 12 months

Price as of 22.10.2026

1 552.10 ₾

VAT included


Current price and stock: online

<https://alldigital.ge/en/sd49225db-hny-2mp-wizsense-ptz-kseluri-martvadi-kamera-25x-opt-gadideb>

Key specs

Megapixels

2 MP

Optical Zoom

25 ×

IP / IK Rating

IP66

Form Factor

PTZ

IR Range

100 m (328.1 ft)

Focal Length

4.8–120 mm

WDR

120 dB

Camera

Image Sensor	1/2.8" CMOS
Max Resolution	1920 (H) × 1080 (V)
Megapixels	2 MP
Form Factor	PTZ
Characteristics	microSD

Lens

Focal Length	4.8–120 mm
Optical Zoom	25 ×
PTZ Presets	300
Pan / Tilt Range	Pan: 0° to 360° endless; tilt: –15° to +90°; auto flip 180°
Aperture	F1.6–F3.5
Field of View	H: 58.5°–2.8°; V: 33.2°–1.5°; D: 67.5°–3.2

Image & Video

Supplement light	Infrared (IR)
Min. Illumination	Color: 0.005 lux@F1.6; B/W: 0.0005 lux@F1.6; 0 lux (IR light on)

Image & Video	
IR Range	100 m (328.1 ft)
Day / Night	Day/Night (auto IR-cut)
WDR	120 dB
Frame Rate	25/30 fps
Compression	Smart H.265+; H.265; Smart H.264+
Audio	
Audio	G.711a; G.711Mu; G.722.1; G.726; MPEG2-Layer2; G.729
Network	
Network Interface	RJ-45 (10/100 Base-T)
Storage	FTP; Micro SD card (512 GB); NAS
Power & Protection	
Power Supply	12 VDC (± 10%),3 A ; POE+(802.3at)
IP / IK Rating	IP66
Power Consumption	20 W
Surge Protection	6 kV
Outputs & Audio	
Audio Input	1 channel (LINE IN, bare wire)
Audio Output	1 channel (LINE OUT, bare wire)
Smart & Features	
Features	Line Crossing, Intrusion Detection
Alarm Input	2 inputs; wet contact (max. 5 mA 3-5 VDC); dry contact
Alarm Output	1 output; dry contact, max. 1,000 mA 30 VDC/500 mA 50 VAC
Connectivity	
Compatible software	DMSS, SmartPSS Lite
Compliance	
Certifications	CE, FCC
Physical	
Operating humidity	≤ 95 %
Operating Temperature	-40 ... +60 °C (-40 ... 140 °F)
Dimensions	Ø160 × 270.4 mm (Ø6.3 × 10.65 in)
Weight	2.4 kg (5.29 lb)